



CRR (FEET) =
DBH (INCHES) x 1.5

NOTES:

1. ALL TREES SHOWN TO BE RETAINED WITHIN THE LIMITS OF CONSTRUCTION ON THE PLANS SHALL BE PROTECTED DURING CONSTRUCTION WITH CHAINLINK FENCING.
2. TREE PROTECTION FENCES SHALL BE INSTALLED PRIOR TO THE COMMENCEMENT OF ANY DEMOLITION WORK (CLEARING, GRUBBING, OR GRADING) AND SHALL BE MAINTAINED THROUGHOUT ALL PHASES OF THE CONSTRUCTION PROJECT. NO CONSTRUCTION MATERIALS, EQUIPMENT, OR SUPPLIES MAY BE STORED IN THE TREE PROTECTION AREA.
3. SEE SPEC SECTION 31 13 16 - SELECTIVE TREE AND SHRUB PROTECTION AND TRIMMING FOR MORE INFORMATION.
4. TRUNK DIAMETER AT BREAST HEIGHT (DBH) MEASURED AT 4.5' ABOVE THE GROUND.
5. TREE PROTECTION FENCE STAKES 8' O.C. MAX.

TREE PROTECTION FENCING
C### NTS

Revisions:

No.	Date:	Description:

Graphic Scale	
DFD Number	
Set Type	
Date Issued	8/1/2017
Sheet Number	